

Bio RS-24, Mini-Rotator for Vacutainers® and Tubes



Vertical rotation 360°



Product video is available
on the website

Bio RS-24 in operation



Mini-rotator **Bio RS-24** provides vertical rotation of the platform. The rotator is an ideal instrument for preventing blood coagulation in tubes and for fulfilment of procedures of biological components extraction.

The device is simple to operate; it is designed as a low cost solution.

Rotator can be used in cold rooms or incubators, operating at ambient temperature range +4°C to +40°C. Low voltage external power supply (12 V) provides electrical safety in humid environment.

Specifications:

Speed control range	5–30 rpm
Vertical rotation movement	overhead, 360°
Digital time setting	1 min–24 hrs / non-stop (increment 1 min)
Overall dimensions (W×D×H)	325×190×155 mm
Weight	1.4 kg
Input current/power consumption	12 V, 110 mA/1.3 W
External power supply	Input AC 100–240 V 50/60 Hz; Output DC 12 V

Catalogue number:

Bio RS-24 with standard platform PRS-22	BS-010133-AAG
PRS-4/12	BS-010117-AK
PRSC-18	BS-010117-EK

Platform	Capacity	Tube Volume	Tube Diameter Ø	Cat. number
1 PRS-22 (standard)	22	1.5–15 ml	10–16 mm	BS-010117-FK
2 PRS-4/12 (optional)	4 and 12	up to 50 and 1.5–15 ml	20–30 and 10–16 mm	BS-010117-AK
3 PRSC-18 (optional)	18	15 ml	15–20 mm	BS-010117-EK

PRS — series platforms are equipped with universal rubber clamps for different size tube fixation;
PRSC — series platforms have metal clamps able to hold heavier solutions (e.g. soil, sand).

1 PRS-22



2 PRS-4/12



3 PRSC-18

